


## Part# RM-24A-R

### Features

- 1U 23.8 inch widescreen LCD Console Drawer
- Screen Pivot with DVI & VGA Port
- 1920 x 1200 WUXGA Ultra high resolution
- Support FHD with 1080p resolution.
- Front 1xUSB, Rear 2xUSB 2.0 Type A, Sharing USB peripheral Device for computer (ex, flash disk, hard driver, KB/Mouse)
- 104-key keyboard with touch pad mouse.
- USB 2.0 Keyboard & Mouse
- Self-locking and auto release rails for convenience.
- Built in 2x 2 watts speakers

### Option

- Composite Video input
- HDMI or Display Port input
- 3G / HD / SD –SDI Broadcast grade input
- 48V, 24V or 12V DC Power



Rear of RM-24A-R

Part No.		
No. of ports		1
KVM Connectors		DVI-D , VGA , USB
LCD	Size	23.8 inch FULL HD display
	Backlight	LED
	Resolution	1920*1080 ( support resolution up to 1920*1200 )
	Max.color	16.7M
	Luminance	250 cd/m2
	View Angel (H/V)	178 / 178
	Contrast Ratio	1000 : 1
Port Selection		N/A
USB HUB		Yes , Front x1 & Rear x 2 USB 2.0 Type A for USB Peripheral Device
Audio		1 x 3.5mm Audio jack
KB/Mouse Emulation		USB 2.0
Rack Depth ( rack cabinet front rails to rear rails )		600mm to 1200mm
Power		100-240V AC 50/60Hz via IEC Type power cord
Environment		Operation temp: 0 to 50 °C Storage temp: -20 to 60 °C Humidity: 10% - 90%, non-condensing Shock: 10G acceleration ( 11ms duration) Vibration: 17 to 500Hz 1G PTP
Physical Dimensions ( W x H x D ) / Net Weights ( KGs )		448x44x690mm / 18 KGs
Packing Dimensions ( W x H x D ) / Gross weights ( KGs )		580x190x840mm / 22 KGs
Accessory		
KVM-2401WPD-M5		1.8meter IEC Type Power Cord x1 , 1.8meter DVI Cable x1 , 1.8meter VGA Cable x1 , 1.8meter USB Cable x1 ,1.8meter Audio Cable x1




Lift the display



Display rotate to the right



Operating position



Rear of RM-24A-R

